

## IN THE CLAIMS

Please replace any previous listing of the claims with the following replacement listing of the claims:

### Replacement Listing of the Claims

1-8. (Canceled)

9. (Currently amended) A multi-domain, wide viewing angle liquid-crystal display, comprising:

- a bottom substrate having a first surface;

- a first transparent conductive layer disposed over said first surface of said bottom substrate;

- a top substrate having a second surface;

- a color filter layer disposed over said second surface of said top substrate;

- a second transparent conductive layer disposed over said color filter;

- a first dry deposited layer over said first transparent conductive layer;

- a second dry deposited layer over said second transparent conductive layer; said second dry deposited layer being spaced adjacent to and facing said first dry deposited layer;

- a plurality of uniformly sized transparent or nontransparent spacers distributed within said space; and

- a liquid-crystal material disposed in the space therebetween;

- wherein each of said first dry deposited layer and said second dry deposited layer is divided into a plurality of pixels each having a boundary and at least two domains; wherein said domains are aligned by a method selected from the group consisting of: mechanical mask, photo-resist, UV treatment, and ridge and fringe field methods;

- wherein said dry deposited layers are exposed to at least a first particle

~~ion beam treatment bombardment~~ and a second ~~particle-ion beam treatment bombardment~~ to selectively align said domains in first and second directions, respectively;

wherein a direction of said first ~~particle-ion beam treatment bombardment~~ with respect to said dry deposited layers is different than a direction of said second ~~particle-ion beam treatment bombardment~~ with respect to said dry deposited layers; and

wherein said liquid-crystal display is operable in the in-plane switching mode.

10. (Cancelled)

11. (Currently amended) The multi-domain, wide viewing angle liquid-crystal display of claim 40, wherein said mechanical mask method comprises: depositing a material on a substrate to form a transparent dry deposited layer;

bombarding said dry deposited layer with said first ~~particle-ion beam treatment~~;

masking said dry deposited layer into first domain areas and second domain areas of the dry deposited layer with a mask; and

selectively bombarding said dry deposited layer with said second ~~particle-ion beam treatment~~ through said mask.

12. (Original) The multi-domain, wide viewing angle liquid-crystal display of claim 11, wherein said material is selected from the group consisting of: hydrogenated diamond-like carbon, amorphous hydrogenated silicon, silicon carbide (SiC), silicon dioxide (SiO<sub>2</sub>), glass, silicon nitride (Si<sub>3</sub>N<sub>4</sub>), alumina (Al<sub>2</sub>O<sub>3</sub>), cerium(IV) oxide (CeO<sub>2</sub>), tin oxide (SnO<sub>2</sub>), zinc titanate (ZnTiO<sub>2</sub>) and a combination thereof.

13. (Currently amended) The multi-domain, wide viewing angle liquid-

crystal display of claim 11, wherein said first ~~particle-ion beam treatment bombardment~~ and said second ~~particle-ion beam treatment bombardment~~ is provided from a source of an ion beam selected from the group consisting of: argon, nitrogen, oxygen, and a mixture thereof.

14-36. (Canceled)

37. (Currently amended) A multi-domain, wide viewing angle liquid-crystal display, comprising:

- a bottom substrate having a first surface;

- a first transparent conductive layer disposed over said first surface of said bottom substrate;

- a top substrate having a second surface;

- a color filter layer disposed over said second surface of said top substrate;

- a second transparent conductive layer disposed over said color filter;

- a first dry deposited layer over said first transparent conductive layer;

- a second dry deposited layer over said second transparent conductive layer; said second dry deposited layer being spaced adjacent to and facing said first dry deposited layer;

- a plurality of uniformly sized transparent or non-transparent spacers distributed within said space; and

- a liquid-crystal material disposed in the space therebetween;

- wherein each of said first dry deposited layer and said second dry deposited layer is divided into a plurality of pixels each having a boundary and at least two domains; wherein said domains are aligned by a method selected from the group consisting of: mechanical mask, photo-resist, UV treatment, and ridge and fringe field methods;

- wherein said dry deposited layers are exposed to at least a first ~~particle-ion beam treatment bombardment~~ and a second ~~particle-ion beam treatment bombardment~~ to selectively align said domains in first and second directions, respectively;

wherein a direction of said first particle-ion beam treatment bombardment with respect to said dry deposited layers is different than a direction of said second particle-ion beam treatment bombardment with respect to said dry deposited layer;

wherein said multi-domain, liquid-crystal display is operable in the in-plane switching mode; and

wherein said multi-domain, liquid-crystal display has a wide viewing angle.

38 and 39. (Canceled)

40. (Previously presented) The multi-domain, wide viewing angle liquid-crystal display of claim 9, wherein said domains of said first and said second dry deposited layers are aligned by said mechanical mask method.

41. (Currently amended) The multi-domain, wide viewing angle liquid-crystal display of claim 9, wherein said first particle-ion beam treatment bombardment aligns first and second ones of the domains of at least one of said pixels in a first direction, and wherein said second particle-ion beam treatment bombardment aligns said first domain in a second direction.

42. (Currently amended) The multi-domain, wide viewing angle liquid-crystal display of claim 41, wherein said second particle-ion beam treatment bombardment overwrites said first direction of said first domain with said second direction.

43. (Currently amended) The multi-domain, wide viewing angle liquid-crystal display of claim 37, wherein said first particle-ion beam treatment bombardment aligns first and second ones of the domains of at least one of said pixels in a first direction, and wherein said second particle-ion beam treatment bombardment aligns said first domain in a second direction.

44. (Currently amended) The multi-domain, wide viewing angle liquid-crystal display of claim 43, wherein said second ~~particle-ion beam treatment bombardment~~ overwrites said first direction of said first domain with said second direction.